## AM MULTIGRAPHICS -- CLEAN N' EASY, 83-6-104059 -- 8520-01-231-6914

Product ID:CLEAN N' EASY, 83-6-104059 MSDS Date:05/01/1992 FSC:8520 NIIN:01-231-6914 MSDS Number: BWPTX === Responsible Party === Company Name: AM MULTIGRAPHICS Address:1800 W CENTRAL RD City:MT PROSPECT State: IL ZIP:60056 Country:US Info Phone Num:708-870-5121 Emergency Phone Num: 708-398-1900 CAGE:0FTL5 === Contractor Identification === Company Name: AM MULTIGRAPHICS Address:1800 WEST CENTRAL ROAD City:MT. PROSPECT State: IL ZIP:60056 Country:US Phone: 708-5121/ EVEN 708-398-1900 CAGE:0FTL5 Company Name: AM MULTIGRAPHICS DIV OF AM INTL INC Address:431 LAKEVIEW CT Box:City:MOUNT PROSPECT State: IL ZIP:60056-6048 Country:US Phone:847-375-1700 CAGE:09177 Ingred Name:VM&P NAPHTHA; (PETROLEUM DISTILLATE) CAS:64742-48-9 Fraction by Wt: 30-35% OSHA PEL:N/K ACGIH TLV:N/K Ingred Name: PUMICE CAS:1332-09-8 Fraction by Wt: 15-20% OSHA PEL:N/K ACGIH TLV:N/K Ingred Name:LANOLIN CAS:8006-54-0 RTECS #:0E3201000 Fraction by Wt: 5-10% OSHA PEL:N/K ACGIH TLV:N/K Ingred Name:3,5-XYLENOL, 4-CHLORO-; (PCMX (GERMICIDAL ANTISEPTIC)) CAS:88-04-0 RTECS #:ZE6850000 Fraction by Wt: <1% OSHA PEL:N/K ACGIH TLV:N/K

Ingred Name: EMULSIFIERS Fraction by Wt: 1-2% OSHA PEL:N/K ACGIH TLV:N/K Ingred Name:WATER CAS:7732-18-5 RTECS #:2C0110000 Fraction by Wt: 30-55% OSHA PEL:N/K ACGIH TLV:N/K LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: EYE: MAY CAUSE IRRITATION. SKIN: MAY DEFAT WITH REPEATED CONTACT. INGESTION: HARMFUL OR FATAL IF SWALLOWED. Explanation of Carcinogenicity:NOT RELEVANT. Effects of Overexposure:SEE HEALTH HAZARDS. Medical Cond Aggravated by Exposure:NONE. First Aid: INHAL: REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O\*2/ARTF RESP) . SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER. CALL MD . EYE:WASH WITH WATER FOR @ LEAST 15 MINUTES. INGEST:DO NOT INDUCE VOMITI NG; CALL PHYSICIAN IMMEDIATELY. Flash Point Method:TCC Flash Point:116F,47C Extinguishing Media: MEDIA SUITABLE FOR SURROUNDING FIRE . Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . SELF EXTINGUISHING AT 121F. Unusual Fire/Explosion Hazard:NONE. Spill Release Procedures: CLEAN WITH WATER, USING PAPER TOWEL. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. Handling and Storage Precautions: AVOID FREEZING OR EXCESSIVE HEAT (110F). STORE IN COOL DRY PLACE. READ & FOLLOW LABEL DIRECTION. DO NOT REUSE CONTAINER. Other Precautions: FOR COMMERCIAL/INDUSTRIAL USE ONLY. KEEP FROM REACH OF CHILDREN. Respiratory Protection:NOT REQUIRED. NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN . Protective Gloves: IMPERVIOUS . Eye Protection: ANSI APPROVED CHEM SAFETY GOGGLES Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health EVAP RATE:SLOWER/WATER (BUTYL ACETATE = 1).

Boiling Pt:B.P. Text:212F,100C Vapor Pres:18 Vapor Density:HVR/AIR Spec Gravity:0.90 (H\*20 =1) Evaporation Rate & Reference:SUPP DATA Solubility in Water:EMULSIFIES Appearance and Odor:VISCOUS, GRITTY BLUE LIQUID

Stability Indicator/Materials to Avoid:YES AVOID CONTACT WITH OXIDIZING AGENTS. Stability Condition to Avoid:NONE KNOWN. Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY PRODUCE CARBON MONOXIDE AND CARBON DIOXIDE.

Waste Disposal Methods: FEDERAL, STATE & LOCAL REGULATIONS FOR LIQUID WASTE SHOULD BE FOLLOWED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.